



274 Church Street
Onehunga

System Control Engineering NZ Ltd

THE GAS BIZZ BULLETIN
February 2010

Training for Plumbers, Gasfitters & Drainlayers Board Courses for 2010

System Control Engineering NZ Ltd will be holding the following PGDB approved courses in February and March 2010

**Commissioning of Over-Pressure Shut Off Regulators
Principles of Flame Safeguard Systems**

8 Credits

10th February 2010

Cost \$ 200.00 + GST

**Regulators & Pipesizing
Function & Use of a Flue Gas Analyser**

8 Credits

10th March 2010

Cost \$ 200.00 + GST



WHERE

Mt Richmond Motor Lodge
676 Mt Wellington Highway
Mt Wellington
Auckland

5.00pm start

Refreshments supplied

FOR BOOKINGS PLEASE CONTACT

Katherine Halloran

Phone: 09 636 1401 - Fax: 09 636 1525

Email: training@systemcontrol.co.nz

System Control Engineering NZ Ltd would like to introduce:



Noble Hack

Noble has joined our company & will be looking after our internal customers on the telephone and in the showroom.

Phone: 09 636 1401 Fax: 09 636 1525

Email: sales@systemcontrol.co.nz

www.systemcontrol.co.nz

WE HAVE THE BELOW LIQUID LEVEL SWITCHES AVAILABLE AT SCE



Level Switch

- Liquids level controller (suitable for clean water, drinking water and general purpose applications)
- Cable length 10 m
- Nominal weight 1.48kg
- Maximum operating temperature 60°C
- Single pole microswitch (10 Amp, 250 VAC)
- Counterweight supplied
- Polypropylene float cover
- IP68 rated
- Dimensions 81 x 131 x 41.5 mm

RSAK053114



Level Switch

- Liquid level controller (suitable for clean water, sewage & waste water applications)
- Cable length 10 m
- Operating density range 0.9 to 1.1 kg / dm³
- Maximum operating temperature 60°C
- Single pole microswitch (10 Amps, 250 VAC)
- Polypropylene float cover
- IP68 rated
- Dimensions 103 mm (diameter) x 163 mm

#RSAK053124

Level Switch

- Liquids level controller (suitable for high temperature applications)
- Operating temperature range -20 to 125°C
- Stainless steel construction
- Operating density range equal to or less than 0.8kg/dm³
- Maximum operating pressure 40 Bar
- Commutation power 60VA
- Float dimensions 50 mm (diameter)
- This level switch is also ideal for use in corrosive liquids

#RSAK053161



SMRV/S100401

Don't forget
we sell
Gas Leak
Detector
Spray



Now only \$8.00+GST+Freight

BACHARACH
Leak Detectors
Flue Gas Analysers

BRAHMA
Pilot Burners
Burner Controls
Ignition Transformers
Gas Solenoid Valves

BROMIC
Appliance Regulators

CAMPINI
Thermostats

CATOBA
Pilots
Controls
Gas Valves

DIGITRON
Digital Manometers

DORMONT
Flexible S.S. Connectors
Quick Disconnect Couplings

DUNPHY
Gas, Oil & Dual Fuel Burners

ECOFLAM
Package Burners

GECA
CO Detectors
Gas Detectors

FLAMEFAST
Hot Metal & Heat
Treatment Equipment

ITAP
Gas Ball Valves

JEAVONS
OPSO Regulators
Appliance Regulators

KROMSCHRODER
Gas Filters
Gas Meters
Pilot Burners
Pressure Switches
Gas Solenoid Valves

MADAS
Gas Filters
Regulators

NAMCO
Combustion Equipment

OARA
LP Gas Regulators

PH PRODUCTS
Smoke Pallets

POLIDORO
Blade Burners
Atmospheric Burners

REGO
LP Gas Regulators

RIELLO
Package Burners

ROBERTSHAW
Pilot Burners
Thermocouples
Gas Control Valves

SATRONIC
Burner Controls

SCE
Test Points
Petes Plugs
Test Nipples
U-Tube Manometers

SEITRON
Gas Detectors

SHERWOOD
Auto Changeover Regulators

SIT
FFD's,
Flame Rods
Gas Controls
Ignition Electrodes

WHITE-RODGERS
Gas Control Valves

Quote of the Month

"The only people who never fail are those who never try"