

Catalogue No: **260-307**

## SCREWLESS TERMINAL 1.5mm 2 CONDUCTOR 18A EARTH GREEN/YELLOW

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Terminals - Screwless > WAGO Screwless Terminals > Series 260,261 and 262 Miniature Terminals - Base Mount > 2 Conductor 1.5mm<sup>2</sup>



Representative Photo Only  
(actual product may vary based on configuration selections)

### Terminal Mod Earth 2.5mm 2 Conductor

- Self-contained cage clamp assembly allows for quick and easy wire termination while ensuring contact quality
- Cage clamp terminals developed to suit a wide range of wire cross sections from 0.08 – 35mm<sup>2</sup>
- Alternate or staggered jumpers made in the field by simply breaking and removing jumper contacts
- Wide variety of terminal sizes and configurations including multiple conductors and decks, earth, sensor, high-current, fused and disconnect terminals
- Modular PCB terminal strips with cage clamp connection in various sizes and pin-spacing to suit any PCB solution
- Multi-connection system and WINSTA plugs and sockets suitable for lighting, power, and control connections
- Full range of accessories to complement any wire-termination solution

#### SPECIFICATIONS

Product Series	260
Component Type Termination Wiring	Terminal
Number of Conductors	2 qty
Number of Potentials	1
Connection / Termination	Cage Clamp Terminal(s)
Colour, Body / Housing	Green & Yellow (Earth) colour
Conductor Entry Position	Side
Conductor Entry Angle	Horizontal
Wire / Conductor Size, Rigid Cable, Min	0.08 mm <sup>2</sup> min
Wire / Conductor Size, Rigid Cable, Max	1.5 mm <sup>2</sup> max
Wire / Conductor Size, Flex Cable, Min	0.08 mm <sup>2</sup> min
Wire / Conductor Size, Flex Cable, Max	1.5 mm <sup>2</sup> max
Wire Strip Length, Min	8 mm
Wire Strip Length, Max	9 mm
Marking Position	Side
Fire Load	0.031 MJ
Mounting	Mounting Accessory (Ordered Separately)
Ex i Suitable	No
IECEX Certified	No
Height	25 mm
Width	5 mm
Depth	17 mm
Weight	0.00158 kg
Certifications	CCA CSA KEMA RoHS UL VDE

Shipping Approvals

ABS (American Bureau of Shipping)  
BV (Bureau Veritas)  
DNV-GL (Det Norske Veritas Germanischer Lloyd)  
KR (Korean Register of Shipping)  
Lloyd's Register of Shipping  
PRS (Polish Register of Shipping)

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	<a href="#">260307_Manufacturer Catalogue</a>